

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)


PCT

(10) International Publication Number
WO 2005/055858 A1

- (51) International Patent Classification⁷: **A61C 8/00**, (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number:
PCT/SI2004/001804
- (22) International Filing Date: 6 December 2004 (06.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0303324-8 11 December 2003 (11.12.2003) SE
- (71) Applicant (for all designated States except US): NOBEL BIOCARE AB (PUBL) [SE/SE]; Box 5190, S-402 26 Göteborg (SE).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): HALL, Jan [SE/SE]; Stabbegatan 2A, S-402 26 Göteborg (SE).
- (74) Agent: OLSSON, Gunnar; Nobel Biocare AB (publ), Box 5190, S-402 26 Göteborg (SE).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: IMPLANT



(57) Abstract: An implant (4) is intended to be fitted in a hole (5) formed in a jaw bone (1). The implant comprises an outer surface (9) which can interact with the soft tissue or connective tissue (2) of the jaw bone and which can be placed at the mouth (6) of the hole. The surface (9) is provided with one or more porous outer layers (10) intended to promote integration between the surface and the soft tissue (2) and to counteract penetration of organisms or bacteria that cause inflammation. By means of this arrangement, continued and substantial integration is maintained between the surface and the tissue. Previous production methods for the implant can be retained with only minor modifications.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Implant

5 The present invention relates to an implant intended to be fitted in a hole formed in a jaw bone. The implant comprises and/or is assigned an outer surface which can interact with the soft tissue or connective tissue of the jaw bone and which can be placed at the mouth of the hole.

10 Implants in dentistry are already well known. The implant is fitted in a hole formed as a threaded hole or as an unthreaded hole. In the latter case, the implant can be provided with its own thread or can be of what is called the self-tapping type. It is already
15 known to provide the implant with a surface at its outer or upper parts to be located at the mouth of the hole when the implant is fitted. It is also already known to provide or arrange the implants with spacers (abutments) for securing the prosthesis that the
20 implant is intended to support. Such spacers can be mounted on the implant or can be produced in one piece with the implant. It is also already known, for various purposes, to provide the surface of the implant with threads and recesses of different types, for example
25 microthreads, and in this context reference may be made to, inter alia, US 5 588 838 and US 6 547 564 B1, WO 03/015654 A1, US 2003/0104338 A1, WO 01/49199 A2 and WO 01/50972 A2. Reference may also be made to the patent applications filed by the same Applicant and to the
30 patents obtained concerning porous layers on implants, for example the porous layers available on the market under the tradename TiUnite®.

35 In this connection, two main problems have to be solved before an entirely satisfactory result can be achieved. The implant must, on the one hand, satisfy the requirement of excellent soft tissue integration between the surface and the soft tissue/connective tissue. On the other hand, the integration has to be

lasting, so as to ensure that large areas of the contact surfaces and upper parts of the implant are not exposed after a certain length of time as a result of bone absorption, which is unacceptable for esthetic reasons, among others. The invention aims to solve this problem. It is also important that the means and measures taken to avoid the occurrence of said disadvantages do not complicate the structure of the implant and its use. The invention solves this problem too.

It should be noted that what is proposed by the invention goes against the prejudices existing in the dental field. Thus, for example, it has hitherto been proposed that the surface in question be subjected to precise machining and/or polishing in order to prevent attack by bacteria and organisms. This machining and/or polishing may in itself work against the integration result. Providing the surface in question with microthreads, for example, means that a point of entry may be created for bacterial attack and bacterial penetration into parts of the implant lying deeper in the jaw bone, giving rise to risks of said bone absorption.

The feature that can principally be regarded as characterizing an implant according to the invention is that the surface mentioned in the introduction is designed or coated with one or more porous outer layers intended, on the one hand, to promote integration between the surface and the soft tissue, and, on the other hand, to counteract accumulation of organisms or bacteria that cause inflammation, so as to ensure continued and substantial integration.

In further developments of the inventive concept, it is proposed to use layers having pores with diameters of ca. 1 μm (micrometer) or less. Thus, for example, pores with diameters of ca. 0.5 μm can be used. Said

embodiments also entail that the porous layer on the surface will have a thickness of at most 5 μm , for example a thickness of ca. 3 μm . The layer of the first surface can also be related to a porosity which is
5 optionally present on the rest of the implant. Thus, the porosity of the first surface can be reduced in relation to the porosity used in the rest of the implant and can be chosen, for example, in the range of 30-40% of the latter. In further illustrative
10 embodiments, a larger area of the part of the implant supporting said surface is used. The first surface can be situated completely or partially on the implant and completely or partially on a part which can be applied to the implant and which can consist of an attachment
15 component, spacer sleeve, etc. After the implant and its soft tissue part have integrated, integration between the first surface and the soft tissue or connective tissue should remain in order to avoid exposure of the underlying implant surface and permit
20 the best possible esthetic result. In experiments, it has previously been shown that a height of the soft tissue above the bone margin should be 1.2 - 2.0 mm, preferably 1.5 - 1.8 mm. Further developments of the inventive concept are set out in the attached dependent
25 claims.

By means of what has been proposed above, a novel approach to the structure and use of implants in dentistry is permitted. The invention goes against the
30 prejudices in respect of the need for a high degree of surface smoothness and instead uses means in the form of a slight porosity in order to promote excellent integration between the surface and the soft tissue, even in the long term. In the case where the implant
35 also has surfaces with a porosity to improve anchoring and, for example, provide a magazine for substances that stimulate bone growth, etc., at parts of the implant located below the surface, technical production can be made relatively simple by using different

degrees of shot-peening and/or etching in different parts of the implant which are to have different degrees of coarseness of the porosity. The already known porosity used for bone-contact surfaces of implants marketed under the tradename TiUnite® can thus still be used, and these are designated here as a coarse porosity. To obtain the novel porosity specific to the actual surface, a porosity is used which is obtained in the same way as the known porosity and which is here called TiUnite® Soft, which has a degree of porosity as in the preferred embodiment of the coarse porosity. By controlling the voltage, current, time and electrolyte composition in the oxidation process, it is possible to control the porosity and structure of the surface so as to achieve optimum soft tissue integration. All or part of said surface can be coated with layers of the lower degree of porosity. The invention also functions in cases where the implants, apart from all or part of said surface, are without porosity.

A presently proposed embodiment of an implant according to the invention will be described below with reference to the attached drawings, in which:

Figure 1 shows a vertical cross section through an implant fitted in a hole in a jaw bone with soft tissue or connective tissue,

Figure 2 shows, partially in vertical cross section and partially in horizontal view, a first porosity on a first surface of the implant according to Figure 1,

Figure 3 shows a vertical cross section and a horizontal view of the porosity on one or more other surfaces of the implant,

Figure 4 shows an enlarged view of parts of the

- 5 -

implant according to Figure 1,

Figure 5 shows a horizontal view of an example of the structure of the porosity of the first surface, at a magnification of 2000 times, and

Figure 6 shows a vertical cross section through a second embodiment of the implant fitted in a hole in a jaw bone with soft tissue or connective tissue.

In Figure 1, a section of a jaw bone is indicated overall by reference number 1. Above the actual jaw bone 3 itself, there is an area of soft tissue or connective tissue 2. An implant 4 is fitted in the jaw bone, specifically in a hole 5 that has been formed in said jaw bone. The implant is provided with upper parts 6 which are arranged at the mouth 5a of the hole. In the present case, the implant is provided with a surface or surfaces 7, and one or more threads 7a by means of which the implant can be screwed into the hole 5. Said upper parts 6 can form part of, or can themselves constitute, a means of securing a symbolically indicated prosthesis 8. Said upper parts 6 have a surface 9 which is completely or partially provided with a porosity 10, shown symbolically in the present case. If the surface 9 is provided partially with a porosity, the latter preferably extends across most of the surface. The porosity can in this case be arranged in bands or islands around and/or along the surface extending peripherally. In Figure 1, a vertical extent for the interacting parts of the tissue 2 and the surface 9 is indicated by H. The interacting parts are indicated symbolically by 11. Said height H in the present case is 1.5 - 1.8 mm. By keeping the height H of the interacting surface 11, downward growth of epithelium is avoided and the upper parts 13 of the implant are not exposed. The implant 4 can be of the

- 6 -

type which, in addition to the porosity 10 on the surface 9, can also comprise one or more other porosities 4a at parts lying below said surface 9. The other porosity can be arranged in a manner known per se and for a purpose known per se.

In Figure 2, a vertical cross section through the porosity 10 is indicated by 14, and a horizontal section of the porosity 10 is indicated by 15. In accordance with the concept of the invention, the depth D of the porosity will be chosen with a value of 5 μm or less, for example 3 μm . The mean diameter d of the pores will be chosen at 1 μm or less, for example 0.5 μm .

In Figure 3, reference number 16 indicates a vertical cross section through the porosity 4a, and reference number 17 indicates a horizontal section of the porosity 7. The porosity 4a is a coarser porosity compared to the porosity 10. In this connection, reference may be made to the TiUnite® implant sold on the market by the Applicant filing the present patent application. In the present case, the depth D' can be 10 μm or more. The mean value of the diameter d' in this case can be 2 μm or more.

Figure 4 shows the structure of an embodiment of the implant 4 diagrammatically. The upper parts 6 of the implant can be regarded as comprising an upper part 6a and a lower part 6b. This implant structure may be used in a certain implantation technique in which one wishes to remove part of the implant during the actual fitting and period of incorporation. The part 6a can thus be fitted onto and detached from the part 6b. It can be applied and detached in a manner known per se, and this does not therefore have to be described in detail here. In accordance with the present invention, it is important that the part 6b remains in its position in which it is fitted from the outset and is not disturbed

during the implantation and period of incorporation. According to the invention, therefore, the interacting surfaces 11 can remain unaffected throughout the implantation. This guarantees an initial high degree of integration between the soft tissue or connective tissue 2. The values of the height H or h can in this way be maintained, and said exposure is avoided. In Figure 4, a small accumulation of bacteria and/or organisms is indicated symbolically by 18. It will be appreciated that said bacteria and/or organisms are easy to remove from the actual space 19 if the surface 6a is smooth and easy to clean. The interacting surfaces 11 constitute an effective barrier against penetration of bacteria and organisms to the underlying parts of the implant. The space in which accumulation possibly takes place is indicated by 19.

Figure 5 shows an example of a porosity which has been produced by means of anodic oxidation and is intended to be arranged on the surface 9 according to Figure 1. As regards the pore diameters and pore depths, reference is made to Figure 2. The figure shows a magnification of 2000 times, and the distance of 10 μm is shown in Figure 1.

In Figure 6, reference number 10' indicates a surface which is lengthened in relation to the surface 10 according to Figure 1. In this case, the length of the implant is shown by L, and the length of the surface by l. The length of the surface 10' coincides substantially in this case with the thickness of the soft tissue 2, but it can alternatively vary slightly from this. In the present case, the interacting surfaces 11 are lengthened, meaning that their height H' considerably exceeds the height H in the illustrative embodiment according to Figure 1. According to the illustrative embodiment, the length l of the surface is at least 1/3 of the total length L of the implant.

The invention is not limited to the embodiment shown by way of example above, and instead it can be modified within the scope of the attached patent claims and the
5 inventive concept.

Patent claims

1. An implant (4) intended to be fitted in a hole (5)
5 formed in a jaw bone (1), and comprising and/or
assigned an outer surface (9) which can interact
with the soft tissue (connective tissue) of the
jaw bone and which can be placed at the mouth (6)
10 of the hole, characterized in that the surface is
completely or partially designed or coated with
one or more porous outer layers (10) intended, on
the one hand, to promote integration between the
surface and the soft tissue, and, on the other
15 hand, to counteract penetration of organisms or
bacteria that cause inflammation, so as to ensure
continued and substantial integration.
2. The implant as claimed in patent claim 1,
20 characterized in that the porous layer (10) is
arranged with pores having mean diameters (d) of
ca. 1 μm or less.
3. The implant as claimed in patent claim 1 or 2,
25 characterized in that the porous layer (10) has a
thickness (D) of at most 5 μm , for example a
thickness of 3 μm .
4. The implant as claimed in patent claim 1, 2 or 3,
30 characterized in that in addition to said surface
(9), here called the first surface, which the
implant comprises and/or is assigned, said implant
has one or more other surfaces which are provided
with a porosity (7) coarser than the porosity of
the first surface, and in that the porosity of the
35 first surface is reduced in relation to the
coarser porosity and is chosen in the range of 30-
40% thereof.
5. The implant as claimed in any of the preceding

patent claims, characterized in that the first surface (9) covers a very large area on an upper implant part, which is up to 1/3 of the total length of the implant.

5

6. The implant as claimed in any of the preceding patent claims, characterized in that the first surface (9) is completely or partially situated on a part which can be applied to the implant or which is produced in one piece with the implant, for example an attachment component (6a), spacer sleeve, etc.

10

7. The implant as claimed in any of the preceding patent claims, characterized in that the implant can be arranged in the bone tissue in such a way that the height of the soft tissue above the bone margin is 1.2 - 2.0 mm, preferably 1.5 - 1.8 mm, so that there will be remaining integration between the first surface (9) and the soft tissue (2), and exposure of the underlying implant sleeve is avoided.

15

20

8. The implant as claimed in any of the preceding patent claims, characterized in that, at its upper/outer portion, it supports and/or interacts with inner and outer parts (6a, 6b), where the inner part (6a) supports the first surface (9) with the porous layer or layers (10), and the outer part (6b) can be temporarily removed during fitting of the implant.

25

30

9. The implant as claimed in any of the preceding patent claims, characterized in that the porous layer (10) of the first surface (9) is based on anodic oxidation.

35

10. The implant as claimed in any of the preceding patent claims, characterized in that, by means of

- 11 -

the porous layer on the first surface (9), it entails only limited outer bone or tissue absorption (12) at the mouth (5a) of the hole.

2 / 3






Fig. 5



3/3

Fig. 6



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/001804

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61C 8/00, A61L 27/56

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61C, A61F, A61L, A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, MEDLINE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0125203 A2 (ROBERT MATHYS CO), 14 November 1984 (14.11.1984), figures 1-2, abstract --	1-10
X	WO 0105325 A1 (CATERINI, RICHARD ET AL), 25 January 2001 (25.01.2001), page 6, line 18 - page 7, line 2, figures 2-3 --	1-10
A	US 6454569 B1 (HOLLANDER ET AL), 24 Sept 2002 (24.09.2002) -- -----	1-10

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

31 March 2005

Date of mailing of the international search report

06 -04- 2005

 Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

 Leif Brander/EX
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/001804

EP	0125203	A2	14/11/1984	CH	658180	A	31/10/1986
WO	0105325	A1	25/01/2001	CA	2378095	A	25/01/2001
				EP	1196111	A	17/04/2002
				FR	2796265	A	19/01/2001
				IL	147662	D	00/00/0000
US	6454569	B1	24/09/2002	AU	1530502	A	05/02/2002
				CA	2414671	A	31/01/2002
				EP	1296612	A	02/04/2003
				IL	153698	D	00/00/0000
				WO	0207634	A	31/01/2002
				AU	3661401	A	20/08/2001
				EP	1255502	A	13/11/2002
				US	6419491	B	16/07/2002
				US	20010039454	A	08/11/2001
				US	20020133232	A	19/09/2002
				US	20040006396	A	08/01/2004
				WO	0158374	A	16/08/2001
				AU	1089995	A	23/05/1995
				CA	2175660	A	11/05/1995
				DE	69433550	D	00/00/0000
				EP	0746273	A,B	11/12/1996
				WO	9512369	A	11/05/1995